

## Chemical Meter - FM Series

- *Simple Small & Rugged Meter with PBT housing.*
- *Mounts on end of hose or a pipe in line.*
- *Local display includes Rate of Flow, Batch and cumulative Totals.*
- *Works well on any pump with flows from 7 -75 LPM*
- *Factory calibrated for thin and medium fluids*
- *Accuracy range:  $\pm 2.0\%$  of reading*



Series		FM-300HL/R
Design		Nutating Disc
Housing		PBT Polyester
Fitting Size	Option 1	1 inch NPT
Flow Range	LPM	7 – 75 LPM
Accuracy		+/-2% of reading
Repeatability		+/- .25%
Pressure Rating	PSIG	50 PSIG
Operating Temperature Range	Celsius	-9 to 54°C
Wetted Components	Housing	PBT Polyester (Valox)
	Seals	Viton
	Nutating Disc	PBT Polyester (Valox)
	Signal Generators	Ferrite (Ceramic Magnet)
Shipping Weight	kg	1.4 kg
Maximum Display	Litres	999999
Power Source		9 volt alkaline battery
Electronic Features	Feature 1	2 Totals(1 Cumulative, 1 Batch)
	Feature 2	Factory Calibration in Gallons or Litres
	Feature 3	Field Calibration Available