

GPI Industrial Meters - PVDF

Features & Benefits

- *Excellent chemical compatibility*
- *Resists abrasion*
- *Lightweight and Durable*
- *Easy Installation*
- *Displays Total, Reset Total & Rate of Flow*



Model No		G2P10IO9LMA
Design		Turbine
Housing		PVDF
Fitting Size		1 inch ISO
Flow Range	LPM	18.9-190 LPM
Accuracy		+/-1.0% of reading (Turbine with Computer)
Repeatability		+/-0.3%
Pressure Rating	bar	10.2 bar
Operating Temperature Range	Celsius	-10 to 60°C
Typical K Factor		550
Wetted Components	Housing	PVDF
Frequency Range	Journal Bearings	Ceramic
	Shaft	Ceramic
	Rotor	PVDF
	Rings	Fluorocarbon
		45-475 Hz @ 5-50 GPM
Strainer Size		28 mesh
Maximum Flow	LPM	284 LPM
Maximum Pressure Drop in 10:1 Range	PSIG	6 PSIG
Weight - Turbine Only	kg	0.58 kg
Weight - Turbine with Computer	kg	0.67 kg
Shipping Weight - Turbine Only	kg	0.77 kg
Shipping Weight - Turbine with Computer	kg	0.86 kg
Electronic Features	Feature 1	2 Totals (1 Resettable/1 Cumulative)
	Feature 2	Factory Calibrate in Gallons or Litres
	Feature 3	2 User Calibrations and Flowrate